

VENEERSTONE

PRODUCT PROFILE:
AUSTIN STONE

# **AUSTIN STONE**

## PROFILE INFORMATION & COLOR OPTIONS

Thick with subtle saw marks and varying dimensions.

### **COLOR OPTIONS**



#### **FLATS**

FLATS: SIZE WILL VARY BY UNIT

LENGTH: 4.5"-19" | HEIGHT: 1.75"-9" WEIGHT: 7 LBS. | THICKNESS: 1.5"

Coverage & packaging based on 1/2" mortar joints.

Packaged in 10 sq. ft. handy box.

#### **CORNERS**

CORNERS: SIZE WILL VARY BY UNIT

HEIGHTS: 3.75"-6" | SHORT RETURN: 2.5"-2.625"

LONG RETURN: 7.625"-9" | THICKNESS: 1.5"

Coverage & packaging based on 1/2" mortar joints.

Packaged in 10 lin. ft. handy box.

# TECH DATA

- Compressive Strength (at 28 days) Meets or exceeds ASTM standard 1800 PSI typical result 5,500 PSI avg. min.
- Water Absorption (at 28 days) Does not exceed 15.2%
- Fireproof? Yes: Will not contribute to smoke or flame development
- · Colorfastness: Existing applications show no undesirable change in coloring after years of weathering



VENEERSTONE.BIZ | 800.781.0277 | LEEBP.COM









