



VENEERSTONE™

PRODUCT PROFILE:
PACIFIC LEDGE

PACIFIC LEDGE

PROFILE INFORMATION & COLOR OPTIONS

Textured with mixed irregular edges and regular cuts with different length and width variations. Clean lines allow for tighter joints giving projects a more modern look.

COLOR OPTIONS




BLUE CREEK

CREEDE

CRESTONE

GENOA*



MINERAL COUNTY

PINE SPRINGS

REDWOOD

FLATS

FLATS: SIZE WILL VARY BY UNIT

LENGTH: 4" - 19" | HEIGHT: 1.5" - 6"

WEIGHT: 7 LBS. | THICKNESS: 1.5"

Packaged in **10 sq. ft.** handy box based 1/2" mortar joints.

CORNERS

CORNERS: SIZE WILL VARY BY UNIT

HEIGHTS: 4" | SHORT RETURN: 2.5"

LONG RETURN: 10.5" | THICKNESS: 1.5"

Packaged in **10 lin. ft.** handy box based 1/2" mortar joints.

TECH DATA

- Compressive Strength (at 28 days) Meets or exceeds ASTM standard 1800 PSI — typical result 5,500 PSI avg. min.
- Water Absorption (at 28 days) Does not exceed 15.2%
- Fireproof? Yes: Will not contribute to smoke or flame development
- Colorfastness: Existing applications show no undesirable change in coloring after years of weathering

Actual product color may vary. We recommend reviewing product samples before making final color selections. All Veneerstone products are CMHA certified and comply with ASTM C1670/C1780. *Some colors are considered premium based on availability and cost increases of manufacturing materials. Visit venerstone.biz for installation guidelines and more information.

VENEERSTONE™

VENEERSTONE.BIZ | 800.781.0277 | LEEBP.COM



MADE IN THE USA



LEE | **BUILDING PRODUCTS®**

©2023 VENEERSTONE BY LEE BUILDING PRODUCTS. ALL RIGHTS RESERVED.