VEREENTERE SHADOW LEDGE

SHADOW LEDGE

PROFILE INFORMATION & COLOR OPTIONS

Various shapes, widths and lengths, creating a variety of overlying shadows on its neighboring pieces of stone. These shadows show more visual interest and depth.

COLOR OPTIONS



FLATS

FLATS: SIZE WILL VARY BY UNIT LENGTH: 4"- 20.75" | HEIGHT: 1"-4" WEIGHT: 7 LBS. | THICKNESS: 1.5"

Coverage & packaging based 1/2" mortar joints. Packaged in **10 sq. ft.** handy box based pm 1/2" mortar joints.

CORNERS: SIZE WILL VARY BY UNIT
HEIGHTS: 1"- 4" SHORT RETURN: 2.25"-2.625"
LONG RETURN: 6"-9.257" THICKNESS: 1.5"

CORNERS

Coverage & packaging based 1/2" mortar joints. Packaged in **10 lin. ft**. handy box based on 1/2" mortar joints.

TECH DATA

- Compressive Strength (at 28 days) Meets or exceeds ASTM standard 1800 PSI typical result 5,500 PSI avg. min.
- Water Absorption (at 28 days) Does not exceed 15.2%
- Fireproof? Yes: Will not contribute to smoke or flame development
- · Colorfastness: Existing applications show no undesirable change in coloring after years of weathering

Actual product color may vary. We recommend reviewing product samples before making final color selections. All Veneerstone products are CMHA certified and comply with ASTM C1670/C1780. *Some colors are considered premium based on availability and cost increases of manufacturing materials. Visit veneerstone.biz for installation guidelines and more information.

VENEERSTONE.BIZ | 800.781.0277 | LEEBP.COM









©2023 VENEERSTONE BY LEE BUILDING PRODUCTS. ALL RIGHTS RESERVED.